

# CONDATO PRIME




Condato Prime is what we call the perfect combination between economy and high quality. It has a load capacity of 500 kg and a total of 30 different platform sizes to choose of which makes it suitable for any type of home. Condato Prime is like the rest of our lift models, based on the screw and nut technology. This means it is easy to install, it runs silently and with low energy costs.

## Lift Shaft Color

### Platform Sizes

Width:  
700-1100 mm  
Depth:  
1100-1600 mm



1000 mm x 1500 mm (Standard)  
1100 mm x 1500 mm (Standard)  
1100 mm x 1600 mm (Standard)

### Standard



RAL 9003

Option



5014



8022



1036



7011

Option



6034



7003




3004



1001

(Choose between 198 different RAL Colors)

### Lift Dimensions



1470 x 1680 mm

### Standard



0702

(Black Rubber)

### Option 1



6172

(Choose between 20 different colors)

### 2



0733

### 3



6173

<b>RECOMMENDED INSTALLATION</b> Indoors and outdoors	<b>DRIVE SYSTEM</b> Screw and nut	<b>PLATFORM BUTTONS</b> Automatic Run All buttons with tactile and braille	<b>BATTERY EMERGENCY LOWERING</b> incl. as standard	<b>MOTOR</b> 2.2 kW
<b>RATED LOAD</b>   500 kg	<b>CONTROL SYSTEM</b>   PLC	<b>CERTIFICATION</b>   MD 2006 / 42 / EC	<b>PIT DEPTH</b>   50 mm	
<b>HEIGHT LIMITS</b> Max travel height 15 meter Top height 2,3 mm	<b>DOOR BUTTONS</b> One touch	<b>RATED SPEED</b>   Max 0,15 m/sec	<b>POWER SUPPLY</b> 220-380V1 or 3-phase 50/60 Hz 16A, frequency converter	
<b>STOPS</b> Max 5 stops 			<b>MANUFACTURED IN SWEDEN</b>	

# STANDARD & OPTIONS

## Door Handle, 30 cm



Black painted (Standard)

Stainless steel (Option)

## Automatic Door Opener

(Option)




## Floor Indicator (Option)



Digital display that indicates which floor the lift is currently standing on.

## Ramp (Option)



If the lift is installed without a pit, a ramp is required according to the EN81.41.

## 2-Way Communication System (Option)



All Condato lifts except Condato Mini are able to install a 2-way communication system which allows access from inside and outside the lift in case of emergency.


## Glass Types



4+4+0,75 mm tempered and laminated safety glass. Select between 4 different types.

- Clear
- Tinted
- Frosted
- Dark Tinted

## Door and Window Frame Colors



Aluminium Color (Standard)

199 Different RAL Colors (Option)

## Side Plate Panel Colors



RAL 9003 (Standard)

199 Different RAL Colors (Option)

## Half Door - Top Floor (Option)

